

Product profile	
Part number	2016-0025
Article name	BioShake D30 elm
Description	Automation friendly Shaker with Edge Locking Mechanism. Designed to be integrated in liquid handling and automation platforms to process labware in chemical and biological laboratories.
Recommended use	Automation Shaking Microplates, DW plates, Extraction protocol
Scope of delivery	BioShake D30 elm External power supply Power cords Europe & US 2x screws to mount device (M3 x 18 DIN 912) Calibration certificate Operation & Integration manual
Conforming use	System is operated by qualified and trained research and laboratory personnel. Applicable safety standards or rules need always be fulfilled.
Country of origin	DE
Customs tariff code	8479 82 00
Mixing	
Frequency range	200 to 2000 rpm with a resolution of 1 rpm
Maximum frequency*	< 225 g: 2000 rpm < 300 g: 1800 rpm < 500 g: 1500 rpm > 500 g: 1000 rpm
Orbit	constant 3.0 mm diameter
Regulation accuracy	± 25 rpm
Acceleration range	1 - 30 seconds with a resolution of 1 second
Zero position	Locked zero position with ± 0.1 mm accuracy
<i>* Feasible frequency heavily depends on load weight and height. Always start with low frequencies and iterate upwards.</i>	
ELM positioning	
Description	Patented Edge Locking Mechanism (ELM) for repeatable and accurate positioning of microplates on a liquid handling or automation platform. With the ELM, labware can either easily be exchanged manually/automatically or it is strongly fixed in a diagonal centered position.
ELM position accuracy	± 0.1 mm
Device control	
Description	Required electronic for remote control is build in the device. No external controller required.
Operation control	Remote controlled as described in the Integration Manual
Peripheral interface	EIA-232 / RS-232 interface (2 m cable with RS-232 plug-in connector) optional: USB via USB-Serial Adapters (Exp. DIGITUS DA-70156) or USB via MOXA USB-to-Serial Hub
Status	LED at front side(GREEN = ok RED = error)
Electrical	
Operating voltage	24 V DC Imax: 3.1 A Peff: 15 Watt Pmax: 75 Watt
Power supply	Input: 100 - 240 V AC 50 - 60 Hz Output: 24 V DC Imax: 5.0 A Pmax: 120 Watt External power supply unit (CE/UL/CSA approved, 85-264 V AC, 47-63 Hz, IEC/EN60320-1 C14 Degree of protection: IP20)
Power connection*	Cable connection length 2 m hollow connector (ID 2.5 mm x OD 5.5 mm)
<i>* Only use the device with the delivered power cord. If another power cord is used ensure the wire diameter is adequate.</i>	
Operating, transport and storage conditions	
Operating range	5 °C - 45 °C (41 - 113 F) 10 - 80 % RH up to 2000 m above sea level non-condensing
Operating conditions	stable (resonance free) horizontal dry inside buildings even
Transportation and storage	-10 °C - 60 °C (14 - 140 F) 10 - 80 % RH non-condensing
General properties	
Housing material	Aluminum anodized
Degree of protection	IP20 (Protected against solid objects up to 12 mm No protection against water)
Pollution degree	1 (no contamination or only dry, non-conductive contamination contamination has no influence)
Airborne sound emission	< 70 db (A)


Dimension and weight

Dimensions	(W x D x H) 142 x 99 x 55.35 mm 5.59 x 3.9 x 2.18 inch
Weight	1.6 kg 3.53 lbs
Packaging size	(W x D x H) 347 x 252 x 131 mm 13.66 x 9.92 x 5.16 inch cardboard box
Packaging weight	3 kg 6.61 lbs

Certifications

Regulatory compliance	2011/65/EU, 2014/30/EU, 2014/35/EU, 2015/863/EU, DIN EN 61010-1:2020-03, DIN EN IEC 61010-2-051:2023-01, DIN EN IEC 61326-1:2022-11, DIN EN 55011:2022-05, DIN EN IEC 63000:2019-05
Patents pending	WO2008135565, US8323588, EP2144716, WO2011113858, US9126162, EP2547431, WO2013113847, US10052598, EP2809436, WO2013113849, US9371889, EP2809435, WO2014207243, US20160368003, EP3013480, WO002022128814A1, WO002022128809A2 Please notify us or our designated agent, if you believe that a user has infringed our intellectual property rights.

Drawing



TECHNICAL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE